



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
29.01.2003 Bulletin 2003/05

(51) Int Cl.⁷: **A61C 17/20, A61C 1/07**

(21) Application number: **02255248.3**

(22) Date of filing: **26.07.2002**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **27.07.2001 US 917101**
03.12.2001 US 336922
04.03.2002 US 90111

(71) Applicant: **Hu-Friedy Mfg. Co., Inc.**
Chicago, Illinois 60618 (US)

(72) Inventors:
 • **Rahman, Anisur Mithu**
Gurnee, Illinois 60031 (US)
 • **Parker, Patricia H.**
Midlothian, Illinois 60445 (US)
 • **Chen, Shu**
Buffalo Grove, Illinois 60089 (US)


(74) Representative: **Fenlon, Christine Lesley et al**
Haseltine Lake & Co.,
Imperial House,
15-19 Kingsway
London WC2B 6UD (GB)

(54) **Ultrasonic inserts**

(57) An ultrasonic insert (20) insertable into a hand-piece for carrying out a dental treatment is easily rotatable by a practitioner with only two fingers. The body of the insert (20) is clamped via a torque lock element (30)

which carries a plurality of radially extending barbs (34b, 34c) which lock a handle thereto. The handle is locked to the torque lock element (30) and is not movable relative thereto either axially or rotatably.

FIG. 16



Description

[0001] The present invention pertains to ultrasonic inserts of a type used in medical/dental treatments. More particularly, the present invention pertains to such inserts with enhanced operating efficiency and user comfort.

[0002] Ultrasonic scalers are used in dental offices for de-plaqueing teeth. Unlike manual scalers, these instruments are powered i.e., the tip of the instrument vibrates at an ultrasonic frequency allowing quick and easy debridement. The operator has less hand fatigue as most of the energy for removing the plaque comes from the generator that powers the instrument. The dental practitioner need only lightly touch the tip of the instrument at an angle to the tooth surface to dislodge the plaque.

[0003] Known ultrasonic scalers, such as scaler 10 illustrated in Fig. 1A of the accompanying drawings, have a handpiece 12a coupled at one end 12a-1 to a cable 12b which includes a hose, to provide a fluid such as water, and conductors to provide electrical energy. The other end of the cable 12b terminates at an electrical generator and fluid source 12c.

[0004] The other end of the handpiece 12a-2 is hollow and is intended to receive a replaceable insert 14 with a transducer 14a (magnetostrictive or piezoelectric) carried on the insert. The transducer 14a extends from a proximal end of the insert 14 into the hollow body 12a-2. An ultrasonically vibrated tip 14b extends from a distal end of the insert. One such insert has been disclosed and claimed in U.S. Patent No. 5,775,901, entitled "Insert For Ultrasonic Scaler", incorporated herein by reference.

[0005] Known magnetostrictive ultrasonic inserts function by exciting a stack of thin nickel plates at a frequency equal to the stack's natural frequency. The excitation is induced through an electrical generator in unit 12c, which supplies a current to a coil embedded in the handpiece. When the insert 14 is placed in the handpiece 12a and the frequency generator 12c is powered on, the operator tunes the generator (manual tuning) until it reaches the resonance frequency i.e., attains the natural frequency of the insert. Alternately, auto-tune units automatically lock on the insert resonance frequency once powered on. At this time, the stack starts vibrating. This vibration of the stack is amplified and transmitted to the tip 14b by means of a connecting body or concentrator. The connecting body is made from material that provides good sound transmission efficiency.

[0006] While the insert 14 is operational, fluid is pumped through the cable-generator system 12b, c and through the handpiece 12a to the tip 14b of the insert 14. The vibrating tip 14b breaks the fluid stream into a spray. The spray not only keeps the tip cool, but also keeps the surface of the tooth cool and provides protection against tissue damage.

[0007] The fluid path through the handpiece 12a needs to be sealed such that no leakage occurs until the

fluid stream exits from the insert at the very tip through a fluid delivery channel. Typically, ultrasonic inserts do not have any moving parts other than the minuscule displacement of the nickel stack, the connecting body or the tip.

[0008] Known magnetostrictive dental scaling ultrasonic inserts used in the U.S.A. are designed to vibrate at 25 kHz or 30kHz frequencies. Another system, popular in Europe, uses a piezoelectric transducer.

[0009] When using an ultrasonic scaler during cleaning, the dental practitioner will need to repeatedly reorient the location of the insert tip 14b with respect to tooth surface depending on which tooth of the mouth is being cleaned. In making this angular adjustment, as illustrated in Fig. 1B of the accompanying drawings, the practitioner will typically take the insert out of the patient's mouth, rotate the insert 14, and tip 14b, inside the handpiece 12a locating tip 14b at a desired angular position. Both hands are used for this rotation as the frictional forces that produce a tight fit of the insert 14 in handpiece 12a must be overcome. During a typical treatment, the process of reorienting the tip must be carried out numerous times. This is not only time consuming but also interrupts the ease and smooth flow of work.

[0010] In areas of the mouth where the practitioner chooses not to rotate the insert 14, the practitioner's wrist must be twisted sufficiently to achieve the same function. This twisting action is opposed by the resistance of the cable 12b, the fluid supply hose and power conductors, which are attached to the handpiece 12a.

[0011] It is desirable to provide ultrasonic scalers which are more comfortable and less fatiguing to use than known instruments. Preferably, any improvements will be downwardly compatible with the numerous generators and handpieces that are already present in dental offices.

[0012] Reference will now be made, by way of example, to the accompanying drawings, in which:

Fig. 1A (as described above) illustrates a previously-proposed ultrasonic scaler having an insert and handpiece;

Fig. 1B (as described above) illustrates one aspect of usage of the insert/handpiece combination of Fig. 1A;

Fig. 2A illustrates an insert embodying the present invention;

Fig. 2B illustrates the insert of Fig. 2A in a handpiece as in Fig. 1A and aspects of usage thereof; Figs. 3A, B and C are various views of the body of an ultrasonic insert embodying the present invention;

Figs. 4A, B, C and D are various views of a snap-fit rotary bearing usable with the body of Fig. 3A;

Figs. 5A, B, C and D are various views of a torque lock embodying the present invention;

Figs. 6A, B and C are various views of a swivel housing used in an embodiment of the present in-

vention;

Figs. 7A, B are various views of a cone usable with an insert embodying the present invention;

Figs. 8A, B and C illustrate steps in assembling an insert embodying the present invention;

Fig. 9A is a side sectional view of an insert embodying the present invention which view illustrates the relationship between the various elements assembled in the steps of Figs. 8A, B and C;

Fig. 9B is an enlarged sectional view illustrating aspects of a section of Fig. 9A;

Fig. 10A is a side sectional view of a handpiece carrying a snap-on adaptor embodying the present invention;

Fig. 10B is an enlarged partial side view of the handpiece and adaptor of Fig. 10A with a previously-proposed ultrasonic insert positioned therein;

Fig. 10C is an over-all view of a previously-proposed insert as shown in Fig. 1 combined with the adaptor of Fig. 10A;

Fig. 11A is an enlarged side view of another embodiment of the present invention;

Fig. 11B is an enlarged partial side sectional view of the insert of Fig. 11A inserted into the handpiece of a previously-proposed ultrasonic scaling unit, generally of the type illustrated in Fig. 1;

Fig. 11C is a side view of a portion of the handpiece of Fig. 11B;

Fig. 11D is a side view of a collar threadable onto the handpiece of Fig. 11B;

Figs. 12A, B are top and side views of a preferred form of an ultrasonic transducer used in an embodiment of the present invention;

Fig. 12C is an end view of the transducer of Fig. 12B;

Figs. 13A-F taken together illustrate a torque lock embodying the present invention;

Figs. 14A-C taken together illustrate a sleeve usable with the torque lock of Figs. 13A-F;

Figs. 15A-E taken together illustrate a cone usable with an insert as in Fig. 2A; and

Fig. 16 is a side sectional view of an insert embodying the invention.

[0013] While this invention is susceptible of embodiment in many different forms, there are shown in the drawing and will be described herein in detail specific embodiments thereof with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the invention to the specific embodiments illustrated.

[0014] A rotatable ultrasonic insert according to one embodiment of the present invention has a body section which carries a bearing for rotatably engaging an ultrasonic handpiece. The body is rotatable, about an axial centerline.

[0015] In this embodiment rotation can be effected by

applying a force only to the insert. In response, the insert rotates but the handpiece does not.

[0016] Preferably, a swivel feature is located at the gripping region of the insert, i.e., close to the treatment tip, where the practitioner would typically position his or her fingers, which allows rotation of the insert by 360 degrees. The swivel also allows rotation of the gripping region and tip without having to rotate the handpiece and/or the supply cord.

[0017] In one embodiment a torque lock is connected to the insert. The torque lock carries an exterior peripheral surface bounded by first and second surfaces. The surfaces protrude from the torque lock generally laterally relative to a center line thereof. At least a position of one of the surfaces is laterally deflectable.

[0018] In one embodiment a handle slidably engages the torque lock. As the handle slides onto the torque lock, it laterally deflects the at least one surface as the handle moves to a position where it is trapped between the two surfaces.

[0019] In an embodiment of the present invention, the tip is rotatable through an arc on the order of at least two hundred seventy degrees.

[0020] In an embodiment of the present invention, the elastomeric member comprises silicone.

[0021] In an embodiment of the present invention, the insert carries a user gripping member for rotating the tip.

[0022] In an embodiment of the present invention, a rotary bearing is positioned adjacent to the elastomeric member whereby the tip and the elastomeric member are rotatable together relative to the handpiece.

[0023] In an embodiment of the present invention, the bearing has an end located adjacent to a region of minimal axial ultrasonic vibration of the insert.

[0024] In an embodiment of the present invention, the instrument includes an elastomeric handle comprising silicone.

[0025] In an embodiment of the present invention, the instrument includes a deformable gripping handle locked to the insert.

[0026] In an embodiment of the present invention, a slot is located on the insert at a region of minimal axial ultrasonic vibration.

[0027] In an embodiment of the present invention, the instrument carries a cylindrical user handle wherein a portion of the torque lock lockingly engages the slot and wherein the bearing member is thereby blocked from axial movement relative to the insert.

[0028] In an embodiment of the present invention, a portion of the handpiece slidably engages the bearing member.

[0029] In an embodiment of the present invention, the grippable member is carried by an element which slidably engages a region of the insert exhibiting minimal vibration.

[0030] In an embodiment of the present invention, the element has first and second sections wherein one section lockingly engages a slot in the minimal vibration re-

gion of the body.

[0031] In an embodiment of the present invention, the second section engages the first section with an interference-fit.

[0032] In an embodiment of the present invention, the second section has a cylindrical external periphery and carries the deformable gripping handle thereon.

[0033] A method of assembling an ultrasonic insert embodying a further aspect of the present invention, comprises:

providing a body portion having a proximal end and a distal end wherein the distal end carries an operating member, the proximal end carries a transducer;

sliding a rotary bearing member over and past the operating member to a location, at least in part, in the vicinity of the proximal end;

sliding a locking member over and past the operating member toward the bearing member and clamping the locking member to the body portion at a region of minimal axial ultrasonically induced vibration thereby blocking axial movement of the bearing member along the body;

sliding a handle over and past the operating member and coupling the handle to the locking member whereby the handle is blocked from any axial movement relative to the body.

[0034] Preferably, in the clamping step, the locating member is positioned to, at least in part, slidably engage with a slot on the body.

[0035] In another aspect of the present invention, an adaptor has an external periphery which can be slidably and releasably inserted into the opening in the handpiece. A standard ultrasonic insert may be inserted through the adaptor into the handpiece. The insert can then be rotated relative to the handpiece with a rotational force applied only thereto. Alternatively, the adaptor can be snap-fitted onto an exterior periphery of a handpiece.

[0036] Fig. 2A illustrates an insert 20 embodying the present invention. The insert 20 includes a transducer 20a which is illustrated as a magnetostrictive transducer. Alternatively, it could be a piezoelectric ultrasonic transducer without departing from the spirit and scope of the present invention.

[0037] The transducer is rigidly coupled to an elongated body 20b which is covered in part by a cylindrical, elongated deformable elastomeric grip 20c. The grip 20c terminates in a cone 20d which is positioned between the grip 20c and operative treatment applying tip 20e.

[0038] The insert 20 operates in accordance with the principles of known ultrasonic dental instruments as discussed above in relation to Fig. 1A. However, insert 20 also carries a rotary bearing 24 which exhibits a hollow cylindrical stem section 24a which defines a cylindrical

region 24b which receives a sealing O-ring 24c. The hollow member 24a terminates at a disc 24d of larger diameter. A planar surface 24d-1 of disk 24 is adjacent to stem 24a.

[0039] As discussed subsequently, when installed on the elongated body 20b, the rotary bearing member 24 is rotatable relative to the body 20b, gripping member 20c and tip 20e. Hence, if the member 24 is fixed, the body 20b, gripping member 20c and tip 20e are readily rotatable therein.

[0040] Fig. 2B illustrates a previously-proposed ultrasonic handpiece 12a, cable 12b and generator 12c, discussed above, of a type typically found in dental offices. An insert 20 embodying the present invention is slidably receivable, in a direction 16a, in the hollow end 12a-2 of the handpiece 12a.

[0041] The cylindrical stem 24a of the rotary bearing 24 slides into the hollow handpiece 12a. The O-ring 24c slidably engages the interior periphery of the handpiece 12a providing a fluid seal and reliably engaging the insert 20 with the handpiece 12a.

[0042] When installed in the handpiece 12a, as illustrated in Fig. 2B, insert 20 can be rotated relative to handpiece 12a with rotary forces applied to the deformable gripping member 20c for purposes of orienting the tip 20e relative to a tooth being de-plaqué. As illustrated in Fig. 2B, the practitioner need not restrain the handpiece 12a while rotating the insert 20. Additionally, insert 20 is relatively rotatable relative to handpiece 12a using only two of the practitioner's fingers. Thus, the orientation of the tip 20e can be continuously altered with only two of the practitioner's fingers, requiring only one hand, while the scaling operation proceeds. This will reduce operator fatigue and substantially shorten the time necessary for the scaling process. The expected torque needed to rotate insert 20 preferably will be less than 2.0 inch-oz.

[0043] When the practitioner has concluded the de-plaqué process, the insert -20 can be removed from the handpiece by pulling it axially from the handpiece in a direction 16b and sterilized. The same insert or a different insert can then be subsequently inserted into handpiece 12a to treat the next patient. It will be understood that the present invention is applicable to ultrasonic inserts which utilize either magnetostrictive or piezoelectric transducers without limitation.

[0044] Figs. 3A, 3B, 3C illustrate different views of the body 20b of the insert 20. As illustrated in Figs. 3A and 3B, body portion 20b is attached to a first end 20a-1 of transducer 20a as would be understood by those of skill in the art. An elongated cylindrical extension 20b-1 extends axially from transducer 20a toward tip 20e.

[0045] The elongated cylindrical metal member 20b-1, as would be known to those of skill in the art, is caused to vibrate axially, in response to electro-magnetic signals received at transducer 20a from handpiece 12a. The signals are produced by generator 12c. This axial ultrasonic vibration is in turn coupled to the tip 20e and

used for effecting de-plaqueing of the subject tooth T, in a spray of fluid M, illustrated in phantom in Fig. 3C.

[0046] A pair of notches 20b-2, 20b-3 is formed on elongated body member 20b-1 in a region of substantially zero axial ultrasonic vibration. While a pair of notches 20b-2, -3 has been illustrated in Fig. 3B, it will be understood that a single notch, or three notches could be used without departing from the spirit and scope of the present invention. Additionally, the exact shape of the generally rectangular notches 20b-2, -3 is not a limitation of the present invention.

[0047] An interior or base plane 20b-2', 20b-3' of each notch 20b-2, -3 is parallel to a plane through the central axis of tip 20e. This notch/tip configuration facilitates energy transmission along insert 20 without increasing the risk of a mechanical fracture due to potential fatigue stress.

[0048] An elongated fluid flow slot 20b-4 extends axially in the region where the body 20b-1 interfaces with the tip 20e. As discussed subsequently, fluid for the spray M flows therethrough.

[0049] Figs. 4A, B, C and D illustrate different views and additional details of rotary bearing 24. As illustrated therein, the cylindrical stem 24a is hollow and defines an interior peripheral surface 24e which is adjacent to the elongated body portion 20b (see Fig. 2A). The bearing member 24 carries a second O-ring 24c-1 in a cylindrical region 24d-2 which is adjacent to a plurality of radially disposed spring-loaded fingers indicated generally at 24g.

[0050] The fingers 24g each terminate at a barbed free end, such as 24g-1, -2, -3 with preferably four such fingers disposed radially about the annular surface 24d-2. Neither the number nor the exact shape of the ends 24g-1, -2 ... -n are limitations of the present invention. As discussed in more detail subsequently, the fingers 24g-1, -2, -3, -4 are deflectable radially inward during assembly and are biased radially outwardly to return to their undeflected condition, illustrated in Fig. 4A, 4B.

[0051] The second O-ring 24c-1 which is positioned adjacent to the annular surface 24d-2 cooperates with O-ring 24c to provide a sealed fluid flow path between handpiece 12a and cone 20d. Cooling fluid flows from handpiece 12a through aperture 24-1 shown in Fig. 4c, and past the fingers 24g-1, -2, -3, -4. It will be understood that the number of fingers 24g is not a limitation of the present invention.

[0052] Figs. 5A-5D illustrate various views of a torque lock 30 which couples a torque, due to the force applied to deformable gripping member 20c by the user's fingers, to the body 20b and treatment tip 20e. The torque lock 30 is preferably molded of a sterilizable thermoplastic which, as discussed below, permits it to deform during assembly without fracturing.

[0053] The torque lock 30 has a hollow body section 32a with an exterior periphery 32b and an internal circumferential periphery 32c as shown in Fig. 5C. The torque lock is molded with a slot 34a formed in the body

32a which permits outward radial deformation of sections 34b and 34c, adjacent to the slot 34a, as the torque lock 30 is slid onto the elongated body portion 20b-1. Surfaces 36a, 36b slidably engage the notches 20b-2, -3 of the elongated member 20b-1. When the notches are so-engaged, the deformable members 34b, c move radially inwardly to a non-deformed condition. In this state, torque lock 30 is locked to the body 20b at the notches 20b-2, -3.

[0054] The interaction between the surfaces 36a, b, in the slots 20b-2, -3 inhibits both rotation and translation of the torque lock 30 relative to the body member 20b-1. Hence, rotating the torque lock 30 will also rotate the body 20b of the insert.

[0055] Once the torque lock 30 has been installed on the body member 20b-1 at the slots 20b-2, -3, it will be fixedly located at a region of substantially zero axial ultrasonic vibration. This minimizes a build-up of heat between the vibrating body 20b-1 and the torque lock 30.

As will be understood by those of skill in the art, in addition to locating the notches 20b-2, -3 at a region of minimal axial ultrasonic vibration, preferably centered on the expected nodal point of zero vibration, the cross section of the connecting body portion 20b-1 through the notches 20b-2, -3 will have a large enough cross-sectional area to transmit ultrasonic vibrations without constriction.

[0056] Figs. 6A, B, C illustrate various views of a housing 40 which is press-fitted over torque lock 30 and which slidably and lockingly engages barbed fingers 24g-1, -2, -3, and -4 of the rotary bearing 24. The housing 40 has an elongated generally cylindrical body 42a with a smooth exterior periphery 42b. The body 42a terminates at an end 42c adjacent to an annular shoulder 42d.

[0057] The shoulder 42d in turn has an end surface 42d-1. When installed, the end surface 42d-1 is adjacent to and rotates relative to annular surface 24d-3 of bearing 24.

[0058] The annular member 42d exhibits an internal cylindrical peripheral surface 42d-2 which traps O-ring 24c-1 in position, forming a fluid seal with bearing 24 when surface 42d-1 is positioned adjacent to surface 24d-3. When so-positioned, the housing 40 can rotate relative to bearing 24 but is not movable axially relative thereto.

[0059] When the housing 40 is rotated relative to the bearing 24, the surface 42d-2 slides over O-ring 24c-1 without excessive friction thereby enabling a practitioner to rotate the tip 20e relative to the handpiece 12a with the use of force applied to elastomeric gripping member 20c by only two fingers.

[0060] The housing 40 has an interior, cylindrical peripheral surface 42b-1 which surface deflects the barbed fingers 24g-1, -2, -3, -4 radially inwardly when the housing 40 is slid onto the fingers 24g. The fingers 24g, which have been inwardly radially deflected by the surface 42b-1 engage a cylindrical slot 42b-2 with a snap fit. The

radially compressed fingers 24g expand outwardly radially and the barbed ends 24g-1, -2, -3, -4 lock into the slot 42b-2 precluding axial motion of the housing 40 away from surface 24d-3 of bearing 24.

[0061] As the housing 40 slidably engages the barbed fingers 24g-1, -2, -3, -4, so the internal cylindrical peripheral surface 42b-3 engages exterior cylindrical peripheral surface 32b of torque lock 30 with a press or interference fit. The press fit between torque lock 30 and housing 40 locks those two parts together precluding either axial linear movement or rotary movement therebetween. The end 42b of housing 40 carries a plurality of threads 42b-4.

[0062] The snap fit between the housing 40 and the rotary bearing 24, in combination with the O-ring 24c-1 provide a sealed fluid flow path from inflow periphery 24e of bearing 24 through outflow end surface 42b-5 labelled on Fig. 6C of housing 40. This fluid flow seal, as noted above, precludes fluid leakage. The exterior cylindrical surface 24g' of each of the fingers 24g rotatably engages the internal cylindrical surface 42b-1 of the housing 40. This provides a pair of rotatable bearing surfaces which permit smooth two finger rotation of the deformable member 20c and the treatment tip 20e. A medically acceptable, sterilizable, lubricant is preferably provided between the bearing surfaces to improve rotational smoothness and to further reduce friction and the required torque.

[0063] Figs. 7A and 7B are views of cone 20d which is carried by rotatable housing 40. Cone 20d has an internal flow path 50a which is sealed by O-ring 50b. Cone 20d includes a set of threads 52. Cone 20d is coupled to housing 40 by the rotatable engagement of threads 42b-4 of housing 40 and 52 of cone 20d.

[0064] The O-ring 50b precludes leakage between an end 50c and a region of body portion 20b-1 which extends therethrough. Fluid exits cone 20d via fluid flow channel 20b-4 in the body portion 20b-1. Fluid exits the cone 20d in the channel 20b-4 as a stream. The stream of fluid impacts the vibrating tip 20e and creates a smooth spray pattern M suited for cooling and cleaning tissues. Adhesives, such as epoxy, can be used to permanently attach the cone 20d to the housing 40.

[0065] Figs. 8A, 8B and 8C illustrate the steps of assembly of the insert 20. Groove 20b'-1 in body section 20b' provides a positive gripping surface usable during assembly by manufacturing fixtures to block axial movement of the insert 20.

[0066] As illustrated in Fig. 8A, initial steps of assembly of the insert 20 include sliding rotary bearing member 24 past operative tip 20e onto body portion 20b-1. The torque lock 30 is then slid onto the operative element 20e and forced along the elongated body 20b-1, which in turn forces elements 34b, c radially outward until surfaces 36a, b thereof slidably engage the slots 20b-2, -3. This slidable engagement with the slots in the body member 20b locks the torque lock 30 to the body member 20b and traps the bearing member 24 against a por-

tion 20b' of the body 20b precluding axial movement thereof. The bearing member 24 continues to be rotatable relative to the elongated body portion 20b.

[0067] As illustrated in Fig. 8B, the housing 40 is then slid onto and past the operative element 20e and forced onto the rotary bearing 24, thereby radially inwardly deflecting the barbed fingers 24g-1, -2, -3, -4 and also press fit onto external peripheral surface 32b of torque lock 30 adjacent to disc 24d. When seated on the bearing member 24, the inwardly deflected fingers 24g expand into radial slot 42b-2, axially locking the housing 40 to the bearing 24 while still permitting relative rotary motion therebetween.

[0068] The circular elastomeric gripping member 20c can be slid onto housing 40 either before or after the cone 20d is threadably engaged therewith. The gripping region 20c has an inner diameter which is slightly smaller than the outer diameter of the housing 40. The member 20c thus elastically attempts to contract around the housing 40 which minimizes unintended slippage of the grip 20c relative to the housing 40. Member 20c can also be permanently attached to housing 40 with adhesive.

[0069] Fig. 9A illustrates a side sectional view of an assembled insert 20 in accordance with the method of steps of Fig. 8A, B and C. Fig. 9B is an enlarged side sectional view of a portion of Fig. 9A further illustrating the relationships of the various elements therein.

[0070] As will be understood by those of skill in the art, preferably tip 20e will be formed and heat treated prior to the start of the assembly process illustrated in Fig. 8A. By forming housing 40 as a separate element from core 20d, their respective lengths are each less than the combined length of 20d and 40. Hence, each can be independently slid over exemplary curved tip 20e even though the assembled combination 20d and 40 will not slide over tip 20e.

[0071] Fig. 10A illustrates a snap-on plastic adaptor 70 which is intended to be used with a standard handpiece, such as the handpiece 12a. As illustrated in Fig. 10A, handpiece 12a includes an annular depression 12c adjacent to open end 12a-2. The adaptor 70 snap-fits onto the handpiece 12a at the groove 12c.

[0072] Adaptor 70 has a body section 72a which carries an annular locking protrusion 72b which slidably engages the slot 12c locking the adaptor 70 thereto. The adaptor 70 also includes a bearing 74a which is carried in an interior region 74b of the body 72a. An O-ring seal 74c can be positioned adjacent to the bearing 74a to minimize the likelihood of leakage from fluid flowing through the handpiece 12a into an insert coupled thereto.

[0073] The insert 70 defines a channel 76a which co-extends with, and abuts, channel 12d in handpiece 12a. The channels 76a and 12d receive a standard insert such as the insert 14 described hereinbefore, which is to be rotatably coupled to handpiece 12a and to be energized thereby.

[0074] Fig. 10B illustrates added details of the insert

14 coupled to adaptor 70 for rotation relative to handpiece 12a. In the embodiment illustrated in Fig. 10B, the adaptor 70 in combination with handpiece 12a and insert 14 provide a sealed fluid flow path between the interior peripheral surface 12b of the handpiece and tip 14b of the insert. In this configuration, a user can rotate insert 14 relative to handpiece 12a by applying rotary forces to the grip 14c in a manner analogous to the way in which rotary forces are applied to the grip 20c of rotatable insert 20 previously described.

[0075] Using insert 70, a standard handpiece, in combination with standard inserts, such as the insert 14, can cost effectively provide improved convenience and comfort for the practitioner. It will be understood that, if desired, the insert 70 could be color coded. The insert 70 can be molded of any sterilizable plastic such as a thermoplastic material commercially available and known as polyphenylsulfone. It will also be understood that a plurality of snap-fit fingers, such as the fingers 72b, can be molded in housing 72a for purposes of releasably attaching the adaptor to the handpiece 12a.

[0076] Fig. 10C is an over-all view of insert 14 coupled to handpiece 12a via adaptor 70.

[0077] Figs. 11A and 11B illustrate an alternate form of an adaptor 80 usable with a handpiece 82. The adaptor 80 includes a cylindrical body section 80a which carries a bearing 80b which could be implemented as a plastic ring bearing. The bearing 80b is carried in a cylindrical slot 80c in housing 80a.

[0078] Housing 80a also carries an O-ring seal 80d in a second slot 80e. Finally, the body 80a terminates at a plurality of deflectable locking fingers 80f. The body 80a is hollow and defines an internal peripheral cylindrical surface 80g.

[0079] Adaptor 80 is slidably receivable into handpiece 82 with a snap-fit. The exterior surfaces of the fingers 80f slidably engage a locking slot 82a formed in an interior peripheral surface 82b of the handpiece 82. The interior peripheral surface 82b also includes a slot 82c for receipt of the O-ring seal 80e, and, a slot 82d which receives the rotary bearing 80b carried by the adaptor 80. It will be understood that the O-ring 80d provides a fluid seal between handpiece 82 and an insert, such as the insert 14 shown in part in phantom, which has been slidably inserted into the adaptor 80 in contact with the internal peripheral cylindrical surface 80g. When so-inserted, the insert 14 can be rotated, along with adaptor 80 relative to the handpiece 82 so as to promote the convenience and comfort of a practitioner. A collar 86 is threadable onto the end of the handpiece 82 to trap the adaptor 80 in place and prevent axial movement thereof.

[0080] Figs. 12A-C illustrate details of a preferred structure of stack 20a. By impressing a "W" bend 20a-1 along the length of each member of the stack, as illustrated, stiffness of the stack can be increased. This in turn promotes continued alignment of the stack relative to central axis HP-A (see Fig. 2B) while the insert 20 is being rotated. The improved alignment minimizes

the likelihood of the stack 20a rubbing against internal peripheral surface 12d during rotation, hence eliminating a possible source of friction and noise.

[0081] Figs. 13A-13F illustrate various details of an alternate torque lock 30'. The torque lock 30' has a hollow body section 32a' with an exterior periphery 32b'. Torque lock 30' is molded with a slot 34a' formed in the body 32a'. The slot 34a' permits outward radial deformation of sections 34b', 34c' adjacent to the slot 34a' as the torque lock 30' is slid onto the elongated body portion 20b-1.

[0082] Surfaces 36a', 36b' slidably engage the notches 20b-2, -3 of the elongated member 20b-1. When the notches are so-engaged, the deformable members 34b', c' move radially inwardly to a non-deformed condition. In this state, torque lock 30' is locked to the body 20b at the notches 20b-2', -3'. The combination of the ends 34b', 34c' with surfaces 36a', b' in the slots 20b-2', -3' inhibits both rotation and translation of the torque lock 30' relative to the body member 20b-1. Hence, rotating the torque lock 30' will also rotate the body 20b of the insert.

[0083] Once the torque lock 30' has been installed on the body member 20b-1 at the slots 20b-2, -3, it will be permanently located at a region Z of substantially zero axial ultrasonic vibration, best seen in Fig. 16. This minimizes a build up of heat between the vibrating body 20b-1 and torque lock 30'. As will be understood by those of skill in the art, in addition to locating the notches 20b-2', -3' at a region of minimal axial ultrasonic vibration, preferably centered on the expected nodal point of zero vibration, the cross section of the connecting body portion 20b-1 through the notches 20b-2', -3' will continue to have a large enough area to transmit ultrasonic vibrations without constriction.

[0084] The torque lock 30' also includes radially deformable collet-like members 30'-1, 30'-2, 30'-3 and 30'-4. The collet-like members are separated by intervening slots 30a, b, c, d which permit deflectable spring-like action in a radial direction. Two of the collet-like members 30'-1, -3 carry a portion of surface 31-1, which terminates at a flange 31-2 on one side, and 31-3 on the other. Two other members 30'-2, -4 are also deflectable laterally. The exterior peripheral surfaces thereof extend to an outer perimeter of flange 31-2 (best seen in Fig. 13D) and prevent rotation of the torque lock 30' relative to housing 40'.

[0085] Figs. 14A, B, C illustrate various views of a housing 40' which is press-fitted over torque lock 30' and which in turn slidably and lockingly engages barbed fingers 24g-1, -2, -3 and -4 of the rotary bearing 24. The housing 40' has a generally elongated cylindrical body 42'a with a smooth exterior periphery 42'b. The body 42'a terminates at an end 42'c, which lies adjacent to an annular shoulder 42'd.

[0086] The shoulder 42'd in turn has an end surface 42'd-1. When installed, the end surface 42'd-1 is adjacent to and rotates relative to annular surface 24d-3 of

bearing 24. Housing 40' rotates relative to bearing 24 and is rotatably coupled thereto as was discussed previously with respect to housing 40 and bearing 24.

[0087] As the housing 40' slidably engages the barbed fingers 24g-1, -2, -3, -4, so the internal cylindrical peripheral surface 42'b-3 slidably engages the exterior surfaces of collet-like members 30'-1, -2, -3 and -4. Interaction between these two sets of surfaces deflects the collet-like members 30'-1, -2, -3, -4 radially inwardly as the surface 42'b-3 slides therealong.

[0088] The surface 42'b-3 slides onto exterior cylindrical surface 31-1 and is trapped by radially extending flange 31-2 and barbs 30'-1a, -1b which move outwardly radially once the surface 42'b-3 abuts flange 31-2. The interaction between the surface 31-1, the radially extending flanges 31-2 and 31-3, the barbs 30'-1a, -1b, along with surface 42'b-3, attach the torque lock 30' to the housing 40' axially and also radially to prevent rotation therebetween.

[0089] Figs. 15A-15E illustrate various views of nose cone 20d' which is threadably attached to housing 40'. Nose cone 20d' also includes a radial slot 20d'-1 for receipt of a sealing O-ring.

[0090] Fig. 16 illustrates additional details of the assemblage incorporating torque lock 30', housing 40', nose cone 20d'. In Fig. 16, the insert 20b is locked to torque lock 30' by radial clamping members 34b', c'. Housing 40' is in turn rotatably coupled to rotary bearing 24 and is locked to torque lock 30', at region 31-1.

[0091] From the foregoing, it will be observed that numerous variations and modifications may be effected without departing from the spirit and scope of the invention. It is to be understood that no limitation with respect to the specific apparatus illustrated herein is intended or should be inferred. It is, of course, intended to cover by the appended claims all such modifications as fall within the scope of the claims.

Claims

1. An ultrasonic dental instrument grippable by an operator comprising:

a handpiece; and an ultrasonic insert with a treatment applying tip, wherein the insert is carried by the handpiece, and, wherein the tip is rotatable relative to the handpiece through an arc on the order of at least two hundred seventy degrees by a force applied only to a portion of the insert wherein the insert includes a torque lock with a plurality of radially movable prongs.

2. An instrument as in claim 1 wherein the insert is releasably coupled for axial insertion into, and removal from, the handpiece.

3. An instrument as in claim 1 or 2 wherein the insert

carries a user comfortable, deformable, elastomeric member whereby the user can rotate the tip relative to the handpiece.

4. An instrument as in claim 3 wherein the insert includes an elongated body with an end coupled to the tip and a torque transferring cylinder coupled between a portion of the body and the elastomeric member whereby the cylinder is mechanically locked to the body by the torque lock such that a rotary force applied to the elastomeric member establishes a torque for rotating the body.

5. An instrument as in claim 4 wherein the cylinder is coupled to the body at a region of minimal axial ultrasonic vibration.

6. An instrument as in claim 4 or 5 which includes a cylindrical bearing which is slidably locked to the handpiece in which the torque transferring cylinder rotates.

7. An instrument as in any one of claims 3, 4, 5 or 6 which includes a rotary bearing positioned adjacent to the elastomeric member whereby the tip and the elastomeric member are rotatably decoupled from, and are rotatable together relative, to the handpiece.

8. An instrument as in claim 7 wherein the bearing is located at least in part, adjacent to a region of minimal axial ultrasonic vibration.

9. An instrument as in claim 1 which includes:

a hollow, generally cylindrical bearing member rotatably latched to the insert wherein the cylindrical bearing member slidably engages the handpiece.

10. An instrument as in claim 9 wherein the insert defines a slot thereon and wherein the cylindrical bearing member is located adjacent to the slot with the torque lock located therebetween.

11. An instrument as in claim 9 or 10 which carries a cylindrical user handle, deformable at least in part, wherein an end of the handle is adjacent to an end of the cylindrical bearing member.




FIG. 1A

FIG. 1B




FIG. 2B




FIG. 2A




FIG. 3A




FIG. 3B






FIG. 3C






FIG. 4D




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D

FIG. 6A




FIG. 6B ← 6C





FIG. 6C






FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D

FIG. 12A



FIG. 12B




FIG. 12C




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E




FIG. 13F




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 15E





FIG. 16





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 5248

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	DE 21 07 526 A (LITTON INDUSTRIES INC) 31 August 1972 (1972-08-31) * page 10, paragraph 2 * * page 11, paragraph 2 * * page 12, paragraphs 1,2 * * page 13, paragraph 2 * * figures 3,4,7,8 * ---	1-11	A61C17/20 A61C1/07
A	US 5 501 596 A (BAILEY RONALD L). 26 March 1996 (1996-03-26) * column 3, line 32-38; figures 6,7,10 * ---	1-11	
A	US 4 634 376 A (EIBOFNER EUGEN ET AL) 6 January 1987 (1987-01-06) * figures * ---	1-11	
P,X	EP 1 180 350 A (HU FRIEDY MFG CO INC) 20 February 2002 (2002-02-20) * the whole document * -----	1-11	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61C
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 7 November 2002	Examiner Fouquet, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.02 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 5248

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-11-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 2107526	A	31-08-1972	DE 2107526 A1	31-08-1972
US 5501596	A	26-03-1996	NONE	
US 4634376	A	06-01-1987	DE 3417123 A1	14-11-1985
			AT 381447 B	10-10-1986
			AT 127385 A	15-03-1986
			CH 668178 A5	15-12-1988
			FR 2563992 A1	15-11-1985
			JP 1792952 C	14-10-1993
			JP 5000062 B	05-01-1993
			JP 60242849 A	02-12-1985
EP 1180350	A	20-02-2002	US 2002040198 A1	04-04-2002
			EP 1180350 A1	20-02-2002
			JP 2002113020 A	16-04-2002
			US 2002127512 A1	12-09-2002

EPO FORM 10459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82